

GENERAL PURPOSE BOX SEALING TAPE



DESCRIPTION

This tape is made of polypropylene film coated with aqueous acrylic adhesive. Resistant to UV and perform under a wide temperature range. Excellent tear and impact resistance. This tape ages well and will not discolour. Available in clear only.

MAIN FEATURES

- Resistance to UV, moisture, cold and weathering.
- Good initial tack, long term adhesion.
- Perform under wide temperature range.
- Clarity: tape stays clear and won't yellow.
- Good strength and impact resistance.

APPLICATIONS

- Packaging, holding and bundling applications where moisture resistance is required.
- Performs well in cold environment (meat, food processing and dairy plants).
- Label protection, surface lamination.
- Single strip closure of regular slotted containers (RSC's) dispensed by hand held box sealer.
- Repair tears in boxes, bags, etc., while in transit or storage.

WILL NOT DISCOLOUR

PERFORMING ADHESIVE

TECHNICAL DATA

Colour	Clear (00)
Backing	Bi-axially Oriented Polypropylene Film
Adhesive	Aqueous Based Acrylic Adhesive
Thickness	1.6 mil
Adhesion to steel	20 oz / in
Tensile strength	20 lb / in
Elongation	160%
Application Temperature.....	7°C (45°F) to 40°C (104°F)
Temperature Resistance	-30°C (-22°F) to 54°C (130°F)

STOCK SIZE

48mm x 100m — 36 rolls/case

48mm x 132m — 48 rolls/case

Please note:

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.