

Automatic Side Seal Machines



INT-20 2 Belt Side Seal

Features the new "APA" technology (Automatic Product Adjustment). Once package size is programmed into machine operator simply pushes a button and the machine will automatically adjust the infeed conveyor position, inverting triangle position for the package size all under 15 seconds. Teflon Coated Rotary wheel side seal after end seal. Speeds up to 40 ppm, Maximum package width 16", 4" minimum package length. Designed for use with all polyolefin films. Polyethylene seal system optional. Maximum package height 6". If products are longer than 4ft. additional exit conveyor necessary. 7" color touch screen with Delta PLC and 12 Program memory. Center Seal Standard, Pin wheel hole punch, Locking casters.

INT-30 2 Belt Side Seal

Same machine as INT-20 2 Belt with wider seal jaw of 30" to accommodate a wide product width. Maximum package width 24"

Side Seal-Continuous Motion



CM-20

The CM-20 is a continuous motion side seal machine with dual servo motor drive. This high speed wrapper can easily run at 50-60 PPM. Features a 7" Delta color touch screen HMI and "APA" Automatic Product Adjustment- The machine will automatically adjust the infeed conveyor, inverting triangle and side seal to the proper position, The CM-20 features a Teflon coated rotary wheel side seal with no maintenance required.

Call (630) 628-6500 for current pricing or more information.