

### *Semi-Automatic Strapping Machines*

#### **PC-101 / SP-1**



#### **Semi-Automatic table top strapping machine with closed cabinet.**

- CE safety standard design
- Safety switch
- Reliable P.C. board electric control
- Hinge type table
- Rigid caster with brake
- Reel unit is core size adjustable design for 8", 9", & 11" diameter

#### **Specifications**

**Strapping Speed:** 2.5 sec/strap (60Hz)  
**Tension:** 30-90 lbs.  
**Sealing Method:** Heating element  
**Strap Sizes:** 1/4", 3/8", 1/2", 5/8" polypropylene;  
**Metric:** 6, 9, 12, 15.5mm polypropylene  
**Core Sizes:** 8"x8", 9"x8", 11"x8"\*  
**Reel Outside Dia.:** 19"  
**Power:** AC 110, 60Hz, 1PH  
**Power Consumption:** 0.57KW  
**Table Height:** 30"  
**Machine Weight:** 220 lbs.  
**Layout Dimension:** 29-1/2"H x 36-1/4"W x 23"

\*Core insert required. Part# 300-1132

#### **PSM1412-IC3A**



The PSM1412-IC3A designed for general purpose semi-automatic strapping. The PSM1412-IC3A has a convenient operator's panel and externally controlled tension. In addition, all electronics are controlled with an integrated circuit control board to minimize down time and maintenance.

#### **Specifications**

**Dimensions:** 35"L x 23"D x 30"H  
**Package Size:** Minimum- 2 1/2"W x 1"H  
Maximum- Unlimited  
**Weight:** 190 lbs.  
**Tension Range:** 10 – 100 lbs.  
**Speed:** 2.5 seconds per cycle  
**Strap Size:** 1/4" – 5/8"  
**Core Size:** 8x8  
(additional 9x8 core is available)  
**Power Requirements:** 110V, 50/60 Hz

Call (630) 628-6500 for current pricing or more information.

Palmer Packaging, Inc.

423 S. Grace Street  
Addison, IL 60101

www.PalmerPackaging.com

Ph: (630) 628-6500  
Fx: (630) 628-7365