

### Shrink Tunnels

---



#### **PP1606-20**

Compact portable Light Duty shrink tunnel with live roller rod conveyor, re-circulating air chamber, digital temperature control, AC variable speed drive conveyor, automatic cool down with shut off. Legs and Locking casters. Available in 110 or 220 volts. \* Also available as table top model.



#### **PP1808-28**

Compact General Purpose medium duty shrink tunnel with live roller rod conveyor, AC variable speed drive, 0 to 95 FPM, variable air velocity control, digital temperature control. Fully re-circulating air system. Automatic cool down with shut off. ½ HP Blower Motor. Locking casters with leveling pads.



#### **PP1808-28SS Stainless Steel**

All Stainless steel frame construction. MFG for USDA approval. Wipe down only. Also available with single viewing window.



#### **PP1808-44**

General Purpose High Capacity shrink tunnel with live roller rod conveyor, AC variable speed drive, 0 to 100 FPM, variable air velocity control, digital temperature control. Fully re-circulating air system. Automatic cool down with shut off. 1 HP Blower Motor. Locking casters with leveling pads.



### **PP1808-44SS**

All Stainless steel frame construction. MFG for USDA approval. Wipe down only. Also available with dual viewing windows.



### **PP2208-48SS Stainless Steel**

All Stainless steel frame construction. MFG for USDA approval. Wipe down only. Available with dual viewing windows.



### **PP2208-48**

Great high performance shrink tunnel with live roller rod conveyor, AC variable speed drive, 0 to 100 FPM, variable air velocity control, digital temperature control. Fully re-circulating air system. Automatic cool down with shut off. 1 HP Blower Motor. Locking casters with leveling pads.



### **PP2612-52**

General purpose High capacity production shrink tunnel with variable air velocity, re-circulating air system, digital temperature control, live roller rod conveyor, AC Variable speed drive 0 to 100 FPM, Automatic cool down with shut off. 1HP Blower Motor, Locking casters with leveling pads.



### **PP3612-60**

High capacity production shrink tunnel with variable air velocity, re-circulating air system, digital temperature control, Heavy Duty 5/8" diameter live roller rod conveyor, AC Variable speed drive 0 to 100 FPM, Automatic cool down with shut off. Dual chamber features Dual 1HP Blower Motor. Dual heater banks, Dual variable air velocity controls, live rollers, and a 60" long chamber.



### **PP4512-60 Large Capacity**

High capacity production shrink tunnel with variable air velocity, re-circulating air system, digital temperature control, Heavy Duty 5/8" diameter live roller rod conveyor, AC Variable speed drive 0 to 100 FPM, Automatic cool down with shut off. Dual chamber features Dual 1HP Blower Motor. Dual heater banks, Dual variable air velocity controls, live rollers, and a 60" long chamber. **Tunnel height available up to 28" tall opening.**



### **PP1808-72 High Speed**

High speed production shrink tunnel with variable air velocity, re-circulating air system, digital temperature control, Heavy Duty 5/8" diameter live roller rod conveyor, AC Variable speed drive 0 to 100 FPM, Automatic cool down with shut off. Dual chamber features Dual 1HP Blower Motor. Dual heater banks, Dual variable air velocity controls, live rollers, and a 72" long chamber.

Call (630) 628-6500 for current pricing or more information.

Palmer Packaging, Inc.

423 S. Grace Street  
Addison, IL 60101

[www.PalmerPackaging.com](http://www.PalmerPackaging.com)

Ph: (630) 628-6500  
Fx: (630) 628-7365