

The Eagle SP11 offers eco-friendly operation through use of two direct-drive 24VDC motors. This eliminates the need for a complex belt and pulley system and provides for nearly silent operation.

Strap tension is controlled electrically, which eliminates the need for a manual spring-based hand crank system.

Just like the Eagle 100, the Eagle SP11 is height adjustable. It includes a stainless steel table top and has a safety switch that cuts power while the lid is open to protect the operator.

- Dual direct-drive 24 volt motors
- "Silent" operation
- Quad locking casters
- Adjustable leg height
- Electronic tension control
- Stainless steel table top
- Safety Switch
- Eco-friendly



Additional information

Power	110VAC, 50/60Hz, 0.25kW
Working speed	3 seconds per strap
Strapping force	0-50kg, 0-110lbs
Strap size	Width (5-15mm) ± 1 mm, Thickness (0.5-0.8mm) ± 0.1 mm, Width (0.20-0.6in) ± 0.04 , Thickness (0.02-0.03in) ± 0.004 in Reel coil of strip width: 160-190mm, 0.6in-7.4in Coil diameter: 200-210mm, External diameter: 400-500mm, 7.9- 8.3in, External diameter: 15.7-19.7in
Outside dimension	L750mm x W550mm x H750mm, L29.5in x W21.7 x H29.5in
Worktable height	750mm, 29.5in
Machine weight	162.8lbs, 74kg
Environment	Humidity $\leq 90\%$, Temperature 0-40°C, 32-104°F
Bottom adhesive	Hot melt: face $\geq 90\%$, width $\geq 20\%$, deviation of position ≤ 2 mm